

# CS 4033/5033 - Machine Learning

AdaBoost Algorithm  
(Yoav Freund and Robert Schapire)

FALL 2020

Input:  $(x_1, y_1), \dots, (x_m, y_m)$ , where  $x_i \in X, y_i \in \{-1, +1\}$ .

Output: A classifier of increased accuracy compared to our weak base classifier.

Initialize:  $\mathcal{D}_1(i) = \frac{1}{m}$  for  $i \in \{1, \dots, m\}$ .

For  $t = 1, \dots, T$ :

- Train weak learner using distribution  $\mathcal{D}_t$ .
- Get weak hypothesis  $h_t : X \rightarrow \{-1, +1\}$ .
- Aim: select  $h_t$  to minimize the weighted error:

$$\varepsilon_t = \Pr_{i \sim \mathcal{D}_t} (h_t(x_i) \neq y_i) .$$

- Choose  $\alpha_t = \frac{1}{2} \ln \left( \frac{1 - \varepsilon_t}{\varepsilon_t} \right)$ .
- Update, for  $i = 1, \dots, m$ :

$$\begin{aligned} \mathcal{D}_{t+1}(i) &= \frac{\mathcal{D}_t}{Z_t} \cdot \begin{cases} e^{-\alpha_t} & \text{if } h_t(x_i) = y_i \\ e^{\alpha_t} & \text{if } h_t(x_i) \neq y_i \end{cases} \\ &= \frac{\mathcal{D}_t(i) \cdot e^{-\alpha_t \cdot y_i \cdot h_t(x_i)}}{Z_t} , \end{aligned}$$

where  $Z_t$  is a normalization factor (chosen so that  $\mathcal{D}_{t+1}$  is a distribution).

Output the final hypothesis:

$$H(x) = \text{sgn} \left( \sum_{t=1}^T \alpha_t h_t(x) \right) ,$$

where  $\text{sgn}(z) = \begin{cases} +1 & \text{if } z > 0 \\ -1 & \text{otherwise} \end{cases} .$